

HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.























XH SERIES **HIGH-VOLTAGE TELEHANDLER**

HANGCHA Family-Design exterior, ergonomic cab, intuitive HMI system and premium driving comfort experience.

HIGH-PERFORMANCE MACHINES IN ANY SITUATION



With permanent magnet synchronous motor (PMSM) technology, can reach top speed: 25 km/h, maximum grade ability: 45%, and industry-leading performance in its class.





THREE STEERING MODES:







The machine is equipped with quick change device, which can realize the quick replacement of different attachments. This enables various operations including fork loading, shovel loading, clamping, aerial work, etc.

The first compact telehandler with 310V high-voltage lithium battery in industry, high voltage DC fast-charging technology. Make a charge from 30% to 80% only in 30 minutes.












Technical data

		Manufacturer		HANGCHA GROUP CO.,LTD.		
		Model		T25-60XHYG	T35-100XHYG	
Lifting capacity		Max.lift capacity	kg	2500	3500	
		Lift capacity at maximum height	kg	2000	2500	
		Lift capacity at maximum reach	kg	800	500	
		Max. lifting height	mm	5800	9800	
		Max. forward reach	mm	3310	7000	
		Load centre distance	mm	500	500	
ight	Α	Front overhang	mm	1000	1240	
	В	Wheelbase	mm	2300	2750	
	С	Tread	mm	1500	1850	
	D	Overall length	mm	3950	5030	
	Е	Fork length	mm	1070	1200	
Μp	F	Overall height	mm	2020	2350	
Dimensions and Weight	G	Overall width	mm	1820	2300	
	Н	Cabin width	mm	810	940	
	J	Min. Ground clearance	mm	240	400	
	К1	Tilt-up angle	۰	12	12	
	K2	Tilt-down angle	۰	117	116	
	L	Min. turning radius	mm	3300	3700	
		Weight	kg	5500	9600	
υ		Tyre type		Vacuum tire	Vacuum tire	
Wheels		Tyre size		12-16.5-14PR /2	400/80-24	
₹		Drive wheel x Steering wheel		4,14	4x4	
		Frame leveling Angle	۰		9	
		Boom lower/raise angle	۰	-2/68	-3.5/62	
		Boom raising time (no load)	s	11	15	
S.		Boom lowering time (no load)	s	8	10	
)ete		Extension time (no load)	s	9	17	
aran		Retract time (no load)	s	9	16	
Performance parameters		Fork backward time (no load)	s	4.5	6	
		Fork forward time (no load)	s	4.5	6	
		Frame leveling time (side to side)	s	/	10	
		Max. travel speed (no load)	km/h	25	25	
		Max. Drawbar pull	N	35000	50000	
		Gradeability	%	45	45	
Motor parameters		Drive motor power	kW	30	45	
		Pump motor power	kW	35	35	
		System voltage	V	310	310	
ers		Battery capacity	Ah	150	173	
Power parameters		Power	kWh	46	53	
		Charger output power 1P220V	kW	3	3	
		Charger output power 3P380V	kW	10	10	









Features

Truck	Standard	Options
Air conditioner		0
Reverse or travel radar sensor		0
Rotating Amber beacon		0
Fire extinguisher in cabin or at rear		0
- 		0
Quick exchange fork carriage	•	
Load backrest	•	
Adjustable suspension seat	•	
Flame retardant leather seats	•	
Traction device	•	
Load moment limiter Overload monitoring devise	•	
Left operable window	•	
Horn	•	
Key switch	•	
Wide angle L/R rearview mirrors	•	
Panoramic reversing mirror	•	
Front wiper with water spray function	•	
Rear window wiper	•	
High and low beam headlights	•	
Front and rear work lights	•	
Norking light	•	
Reverse light	•	
Windshield protective frame		0
Fire Extinguisher		0
Foam filled tire		0
Quick change heavy Duty Multi-Purpose Bucket		0
Quick change soft bale clamp		0
Quick change crane arm		0
Forklift arm		0
Steering		
Three steering modes	•	
Adjustable steering column	•	
Hydraulic	'	
Hydraulic quick coupler	•	
Tilt cylinder self-locking valve	•	
Self locking valve for telescopic oil cylinder Lifting cylinder self-locking valve	•	
Lifting cylinder seit-locking valve Lifting cylinder maintenance arm	•	
Hydraulic Oil Filter	•	
Hydraulic oil air filter	•	
Hydraulic oil dipstick		
Power		
2WD and 4WD switch function	•	
Three gears	•	
Transmission		
Wet brake	•	
wet til ake Limited slip differential		
Hydraulic power steering		
Control		
Dual axis proportional control handle	•	
Emergency stop switch	•	
Parking brake	•	
Safety		
Warning light	•	
Reverse alarm	•	
Reverse alarm Reverse camera		0
Reverse camera Reverse radar		0
		<u> </u>
Accept various attachments		
		0
		0
Fork-Mounted Extendable Truss		0
Fork-Mounted Extendable Truss Fork-Mounted working platform Bucket		

Electronics	Standard	Options
Build-in charger	•	
DC fast charging port	•	
Fault self diagnosis function	•	
7-inch color multifunctional display screen	•	
Motor temperature display	•	
Warning lamp for not fastening the seat belt	•	
Water cooling system	•	
Heater	•	
Reading light	•	
Radio	•	
LISB charge nort	•	

